


SPECIFICATIONS



	TITAN 6	TITAN 8	TITAN 9	TITAN 10	TITAN 12	TITAN 15	TITAN 17
Capacity (Heaped)*	215 ft ³	280 ft ³	320 ft ³	348 ft ³	414 ft ³	543 ft ³	607 ft ³
Capacity with side extensions (Heaped)*	263 ft ³	345 ft ³	387 ft ³	423 ft ³	510 ft ³	634 ft ³	710 ft ³
Overall Height (A)	9'9"	9'9"	10'6"	10'10"	10'10"	11'9"	11'9"
Overall width (with standard tires) (B)	8'4"	8'4"	8'4"	9'6"	9'6"	9'6"	9'6"
Loading Height (with std. wheels)** (C)	6'3"	6'3"	6'8"	7'4"	7'4"	8'3"	8'3"
Overall Length (D)	19'8"	23'	23'	23'	25'7"	26'	27'11"
Internal Length	10'8"	13'8"	14'0"	13'6"	16'	16'6"	18'4"
Internal width	59"-67"	59"-67"	59"-67"	59"-75"	59"-75"	59"-75"	59"-75"
Internal height	33"	33"	39"	39"	39"	52"	52"
Standard tire size***	18.4-34	18.4-34	18.4-34	580/70 R38	580/70 R38	580/70 R38	580/70 R38
Unladen Weight	7,452 lbs	8,069 lbs	8,554 lbs	11,486 lbs	12,059 lbs	13,845 lbs	14,462 lbs
Steel thickness (floor / sides)	1 ¹ / ₆₄ "	1 ¹ / ₆₄ "	1 ¹ / ₆₄ "	1 ³ / ₆₄ " / 1 ¹ / ₆₄ "	1 ³ / ₆₄ " / 1 ¹ / ₆₄ "	1 ³ / ₆₄ " / 1 ¹ / ₆₄ "	1 ³ / ₆₄ " / 1 ¹ / ₆₄ "
Axle Size	3 5 ³² "	3 5 ³² "	3 5 ³² "	2" x 2"	2" x 2"	2 7 ¹⁶ " x 2 7 ¹⁶ "	2 7 ¹⁶ " x 2 7 ¹⁶ "
Brake Size / Axle Studs	15 3 ⁴ / ₄ " x 3 5 ³² " 8 stud	15 3 ⁴ / ₄ " x 3 5 ³² " 8 stud	15 3 ⁴ / ₄ " x 3 5 ³² " 8 stud	15 3 ⁴ / ₄ " x 3 5 ³² " 10 stud	15 3 ⁴ / ₄ " x 3 5 ³² " 10 stud	16 1 ¹ / ₅ " x 5 3 ³ / ₆₄ " 10 stud	16 1 ¹ / ₅ " x 5 3 ³ / ₆₄ " 10 stud
Floor - Chain Diameter	15 5 ³² "	15 5 ³² "	9 1 ⁶ / ₁₆ "	9 1 ⁶ / ₁₆ "	9 1 ⁶ / ₁₆ "	23 5 ³² "	23 5 ³² "
PTO Speed	540rpm	540rpm	540rpm	1000rpm	1000rpm	1000rpm	1000rpm
Bed drive shaft diameter	2"	2"	2 1 ⁴ / ₄ "	2 1 ⁴ / ₄ "	2 1 ⁴ / ₄ "	2 5 ³² "	2 5 ³² "
Minimum recommended HP	80HP	90HP	100HP	120HP	140HP	150HP	170HP

Key: * For capacity calculation see page 3. ** Add 12" for side extensions. *** Contact us for other tyre sizes

Standard/Optional Equipment	TITAN 6	TITAN 8	TITAN 9	TITAN 10	TITAN 12	TITAN 15	TITAN 17
*Side Extensions	☐	☐	☐	☐	☐	☐	☐
Electronic Bed Speed Control	☐	☐	☐	☐	☐	☐	☐
Compost/Poultry Manure Beater Tips	☐	☐	☐	N/A	N/A	N/A	N/A
Flashing LED Strobe Light	☐	☐	☐	☐	☐	☒	☒
Sprung Drawbar	N/A	N/A	N/A	☐	☐	☒	☒
Commercial Axle - Air / Hydraulic Brakes	N/A	N/A	N/A	☐	☐	☒	☒
ISOBUS Variable Weigh Cell System	N/A	N/A	N/A	☐	☐	☐	☐
Slurry Door	☒	☒	☒	☒	☒	☒	☒
Oversize Wheels	N/A	N/A	☐	☐	☐	☐	☐
WAJ PTO with Cam Clutch	☒	☒	☒	☒	☒	☒	☒

Key: ☐ Optional Equipment ☒ Standard Specification N/A Not Available

The company's policy is one of continuous improvement and development, therefore specifications are subject to change without prior notice.